



Applications and installation

- 1-Water Supply
- 2-Pressure Boosting

Operation conditions

- 1- Min well diameter : 4"
- 2-Max liquid temperature + 60 C

Components

- 1- Pump external casing : AISI 304
- 3-Delivery Casing : AISI 304
- 2-Diffuser : AISI 304
- 3-Impeller : AISI 304



TYPE	HP	INCH		DELIVERY (m3/h)					
				0	1,8	2,4	3	3,6	4
4 PF 3-09	0,75	11/4"	MSS	57	47	44	35	30	19
4 PF 3-12	1			77	64	58	47	43	28
4 PF 3-15	1,5			97	83	77	67	57	40
4 PF 3-18	1,5			116	97	90	77	67	45
4 PF 3-22	2			143	120	110	90	80	54
4 PF 3-25	2			160	134	124	110	90	60
4 PF 3-29	3			185	155	143	120	103	70
4 PF 3-33	3			211	177	164	130	118	80
4 PF 3-39	4			252	213	195	145	138	94
4 PF 3-45	4			288	243	224	195	162	110
4 PF 3-52	5,5	334	282	261	230	184	123		

TYPE	HP	INCH		DELIVERY (m3/h)					
				0	3	4	4,5	5	6
4 PF 5-08	1	11/4"	MSS	52	41	36	33	26	23
4 PF 5-12	1,5			77	63	56	50	45	37
4 PF 5-17	2			108	88	77	70	64	54
4 PF 5-21	3			134	108	96	87	77	67
4 PF 5-25	3			157	127	113	103	90	78
4 PF 5-33	4			209	168	149	137	125	105
4 PF 5-38	5,5			242	194	172	158	140	123
4 PF 5-44	5,5			279	226	202	187	150	143
4 PF 5-52	7,5			330	267	239	221	190	169

TYPE	HP	INCH		DELIVERY (m3/h)					
				0	6	7	8	10	12
4 PF 8-07	1,5	2"	MSS	41	34	32	27	22	17
4 PF 8-10	2			58	46	43	38	32	25
4 PF 8-12	3			71	55	52	47	42	31
4 PF 8-15	3			87	68	64	57	50	38
4 PF 8-18	4			104	84	79	72	60	47
4 PF 8-21	5,5			122	98	93	85	70	55
4 PF 8-25	5,5			144	114	107	97	82	64
4 PF 8-30	7,5			174	139	131	120	102	79
4 PF 8-37	7,5			215	169	160	145	122	93
4 PF 8-44	10			256	201	190	172	142	111

TYPE	HP	INCH		DELIVERY (m3/h)					
				0	8	10	12	15	18
4 PF 18-05	2	2"	MSS	33	32	28	26	22	16
4 PF 18-07	3			46	42	40	36	30	20
4 PF 18-10	4			65	62	57	52	43	29
4 PF 18-13	5,5			84	80	74	67	56	38
4 PF 18-18	7,5			117	114	102	93	77	54
4 PF 18-25	10			163	152	141	129	107	75