

ALL STAINLESS STEEL



Applications and installation

- 1-Water supply systems
- 2-Pressure boiler feeding
- 3-Pure water treating systems
- 4-Refining chemical industries

Operation conditions

- 1- Liquid temperature: -15°C~+110°C
- 2-Maximun Ambient temperature : +50°C

Components

- 1-Casing, impeller, back-cover : SS 304
- 2-Pump shaft and guide plate : SS 304



Vertical Multi-stage Stainless Steel Pumps

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	1,6	2	3	3,6	4
DKP 310	1	1"	Hm	70	59	57	47	39	31
DKP 315	1,5			95	88	84	69	57	46
DKP 319	2			120	112	107	88	72	58
DKP 325	3			158	147	141	116	94	76

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	2,5	4	6	7	8
DKP 510	2	1 1/4"	Hm	72	62	58	49	42	34
DKP 516	3			110	99	93	80	69	64
DKP 520	4			138	124	117	100	86	71
DKP 526	5,5			178	161	153	130	113	93

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	5	7	10	11	12
DKP 806	3	1 1/2"	Hm	68	62	56	51	43	39
DKP 808	4			90	81	75	64	58	52
DKP 810	5,5			113	101	93	80	73	65
DKP 814	7,5			158	141	131	112	102	91
DKP 816	7,5			175	161	149	128	117	104

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	7	10	12	14	16
DKP 1205	4	2"	Hm	65	60	55	50	43	35
DKP 1206	5,5			80	72	66	60	52	42
DKP 1208	7,5			100	96	88	80	70	56
DKP 1210	10			125	120	111	101	88	72

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	8	14	18	20	22
DKP 1604	5,5	2"	Hm	60	54	49	43	38	34
DKP 1606	7,5			89	82	74	64	58	52
DKP 1608	10			115	110	99	86	79	70
DKP 1610	15			145	138	125	109	100	88

TYPE	HP	DN		DELIVERY (m3/h)					
				0	16	28	32	36	40
DKP 3204	10	DN 65	Hm	82	72	59	53	47	37
DKP 3206	15			120	108	90	81	72	57