



### Applications and installation

- 1-Water supply systems
- 2-Pressure boiler feeding
- 3-For domestic use, for civil and industrial applications.

### Operation conditions

- 1- Liquid temperature: +40°C
- 2-Maximun Ambient temperature : +40°C

### Components

- 1-Impeller : PPO Plastic
- 2-Diffusers : PPO Plastic

### Motor

- 1-230 V OR 380 VOLT
- 2- 50 HZ
- 3- 2850 RPM



Vertical Multi-stage Pumps									
TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	2,5	3,5	5	6	7
<b>DMK 707</b>	2	11/4"-1"	H/M	69	60	52	40	25	12
<b>DMK 708</b>	2,5	11/4"-1"		80	70	60	47	27	13
<b>DMK 709</b>	3	11/4"-1"		90	79	68	50	28	14

  

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	3,5	5	6	7	9
<b>DMK 908</b>	3	11/2"-11/4"	H/M	83	70	62	48	38	23
<b>DMK 909</b>	4	11/2"-11/4"		94	77	67	52	42	26

  

TYPE	HP	OUTLET INCH		DELIVERY (m3/h)					
				0	6	8	10	12	16
<b>DMK 1604</b>	5,5	2"	H/M	80	75	71	66	59	40
<b>DMK 1606</b>	7,5	2"		120	110	104	98	88	60
<b>DMK 1608</b>	10	2"		160	148	140	130	118	80