

SUBMERSIBLE SEWAGE PUMPS

DVX 80 - DVX 100

Applications and installation

1-These pumps are used for transfer of sewage and rain water, The float switch can automatically control on and off with the change of the liquid level. The protector in the motor can automatically cut off the power when it is overheated or overcurrented, thus guarantee the security and reliability of pump's run even in the atrocious environment.



TECNICAL DETAILS

| Model : | DVX 80 | DVX 100 |
|-------------------------|--------------------------|--------------------------|
| Power(hp) : | 0,8 | 1 |
| Outlet diameter(mm) : | 50 | 50 |
| Voltage(V/Hz) : | 230/50 | 230/50 |
| Max.flow(l/min) : | 200(12m ³ /h) | 300(18m ³ /h) |
| Max.head(m) : | 9 | 10 |
| G.W.(kg) : | 19 | 22 |
| Max diam. particuls(mm) | 25 | 25 |
| Dimensions(cm) : | 26.0X19.5X50.0 | 26.0X19.5X54.0 |

| SUBMERSIBLE SEWAGE PUMPS | | | | | | | |
|--------------------------|-----|----|-----|------------------------------|---|---|----|
| TYPE | HP | DN | | DELIVERY (m ³ /h) | | | |
| | | | | 0 | 3 | 6 | 10 |
| DVX 80 | 0,8 | 2" | MSS | 9 | 7 | 6 | 4 |
| DVX 100 | 1 | 2" | | 10 | 9 | 8 | 7 |
| | | | | 6 | 7 | 6 | 4 |

