

CENTRIFUGEL PUMPS

Applications and installation

The TSP series pumps are recommended for pumping clean water and chemically non-aggressive liquid. They have compact size and are extremely reliable, very simple to use, efficient and almost maintenance-free. They are suitable for boosting pressure water supplying for household, irrigation, general industrial applications, etc...

Construction features

Max ambient temperature up to 40°C
 Max fluid temperature up to 40°C
 Max pressure up to 10 bar
 230-380 VOLT 50 HZ

Operating Limitations

Pump Body: cast iron
 Wire: % 100 Copper
 Shaft: stainless steel
 Impeller: brass
 Protection Class: IP44



TSP 150
TSP 200



TSP 300



CENTRIFUGEL PUMPS									
TYPE	HP	iNÇ.		DELIVERY (m3/h)					
				0	6	12	18	20	24
TSP 100	1	1 1/2"	Hm	19	13	6			
TSP 150	1,5	2"		18	15	13	12	10	8
TSP 200	2	2"		19	18	15	13	12	9

TYPE	HP	iNÇ.		DELIVERY (m3/h)					
				0	6	12	18	20	24
TSP 300	3	2"	Hm	30	29	27	24	22	19

Type	Power		R.P.M	Q.max (l/min)	H.max (m)	S.Head (M)	N.W(kg)	PACKAGE DIMENSION&GW				H	A	B
	HP	kW						A	B	H	Kg			
TSP 100	1	0.75	2850	210	19	6	12	310	175	210	13			
TSP 150	1,5	1,1	2850	430	18	6	21	390	243	245	22			
TSP 200	2	1,5	2850	450	19	6	24	390	243	245	25			
TSP 300	3	2,2	2850	450	29	6	25	400	235	300	26			

