

#### Properties

- 1-Shaft and motor connection flange as NEMA standar 4-Max. water heat 40 C
- 2-Water coolant system
- 3-Unlimited immersion depth
- 4-Max. water heat 40 C
- 5-Rewindable motor



	TİP	HP	KW	KG	AMP.	ÇAP	KALKIŞ
5"	5 DT 550	5,5	4	38	11	123 mm	DİREK
	5 DT 750	7,5	5,5	38	14		
	5 DT 1000	10	7,5	42	16		
	5 DT 1250	12,5	9,2	44	20		
	5 DT 1500	15	11	48	25		
	5 DT 1750	17,5	13	54	28		YILDIZ
	5 DT 2000	20	15	58	33		
	5 DT 2500	25	18,5	58	39		
	5 DT 3000	30	22	58	48		

	TİP	HP	KW	KG	AMP.	ÇAP	KALKIŞ
6"	6 DT 550	5,5	4	46	11	145 mm	DİREK
	6 DT 750	7,5	5,5	46	13		
	6 DT 1000	10	7,5	48	18		
	6 DT 1250	12,5	9,2	50	22		
	6 DT 1500	15	11	56	26		
	6 DT 1750	17,5	13	60	29		
	6 DT 2000 D	20	15	66	33		
	6 DT 2000 Y	20	15	66	33		
	6 DT 2500	25	18,5	72	41		
	6 DT 3000	30	22	82	48		
	6 DT 3500	35	26	88	56		
	6 DT 4000	40	30	98	65		
	6 DT 5000	50	37	106	77		
	6 DT 6000	60	45	116	95		

	TİP	HP	KW	KG	AMP.	ÇAP	KALKIŞ
7"	7 DT 3000	30	22	110	49	165 mm	YILDIZ
	7 DT 4000	40	30	118	64		
	7 DT 5000	50	7,5	130	78		
	7 DT 6000	60	9,2	140	92		
	7 DT 7000	70	11	148	109		
	7 DT 7500	75	15	154	113		
	7 DT 8000	80	18,5	158	123		
	7 DT 9000	90	22	171	138		

	TİP	HP	KW	KG	AMP.	ÇAP	KALKIŞ
8"	8 DT 30	30	22	112	51	195 mm	YILDIZ
	8 DT 40	40	30	131	63		
	8 DT 50	50	37	163	79		
	8 DT 60	60	45	145	96		
	8 DT 70	70	52	162	109		
	8 DT 75	75	55	169	117		
	8 DT 80	80	59	175	121		
	8 DT 90	90	66	187	138		
	8 DT 100	100	75	200	156		
	8 DT 110	110	81	213	168		
	8 DT 125	125	92	235	188		
8 DT 150	150	110	269	226			

	TİP	HP	KW	KG	AMP.	ÇAP	KALKIŞ
10"	10 DT 125	125	92	330	190	232 mm	DİREK
	10 DT 150	150	110	330	230		
	10 DT 180	180	132	370	278		
	10 DT 200	200	147	400	305		
	10 DT 225	225	165	464	345		
	10 DT 250	250	185	464	380		